



**Max. flow**  
4.8GPH(18L/H)



**Sound Level**  
17-19dB(A) @ 3.3ft(1M)



**Max. discharge Head**  
39.4ft(12M)

### Features

- Capacitive Sensor
- Built-in Operation Tracking
- Variable Flow Rate
- Ultra-quiet Operation
- Diagnostic LED
- Up to 54,600Btu/h / 16kw
- Slim Design for Easy Installation

### Specification

Model	NUSL-39FA
Power Supply	115V&230V 50/60Hz
Power	<4W
Max. flow	4.8GPH(18L/H), range from 3.2-4.8GPH(12-18L/H)
Sound Level	17-19dB(A) @ 3.3ft(1M)
Max. discharge Head	39.4ft(12M)
Max. suction Lift	6.6ft(2M)
Max. unit Output	54,600Btu/h(16kw)
Safety Switch	3A Normally Closed
Max. water Temperature	104°F(40°C)
Discharge Tube	1/4in(6mm) ID
Class	II appliance <input type="checkbox"/>
Rated	Continuous
IP Protection	Fully potted, IP-45
L × W × H (inch)	7-3/8inch × 1-1/8inch × 1-1/8 inch
L × W × H (mm)	187mm × 29mm × 29mm

### Dimension and Typical Performance

